

## Load test on Lifting device 5711-050 X-lyft / X-2500

(3 appendices)

### 1. Summary

RISE have on commission by Lundmark Safety Technologies AB performed load test on Lifting device 5711-050 X-lyft / X-2500, called X-lyft further in the report, see figure 1 and appendix 1 for the X-lyft. Testing was carried out in RISE facilities in Skellefteå on the large test beam. The test item was provided by Lundmark Safety Technologies AB.

The X-lyft is marked with working load limit of 2 500 kg and is tested to manage 1,5 times the work load which is 3 750 kg (36 825 N). The X-lyft manage this load without any permanent deformations.

Table 1. Loads in lifting test.

Test no.	Lifting method	Load (kg)	Load (N)	Comments
1	Lifting strings	3 750	36 825	No visible deformations
		5 500	54 010	Small twist in pos 2
		6 500	63 830	Permanent flat vice deformation, 7 mm on pos 2
2	Lifting hooks	3 750	36 825	No visible deformations
		5 500	54 010	small twist in pos 2

Measurement uncertainty is a measure of the correspondence between the measurement value and the true value of the measurement variable. The measurement uncertainty has been calculated with a 95% confidence interval.




Figure 1. X-lyft.

### RISE Research Institutes of Sweden AB

Postal address  
 Box 857  
 501 15 BORÅS  
 SWEDEN

Office location  
 Laboratorgränd 2C  
 931 77 Skellefteå  
 SWEDEN

Phone / Fax / E-mail  
 +46 10-516 50 00  
 +46 33-13 55 02  
 info@ri.se

This document may not be reproduced other than in full, except with the prior written approval of RISE Research Institutes of Sweden AB.

## 2. Lifting test

### 2.1 Test samples

One X-lyft that is marked for working load limit of 2 500kg was tested for safety load, 1,5 times marking load. The X-lyft was also tested for higher load.

The X-lyft is compliance to the Machinery Directive 2006/42/EC clause 4.1.2.3 Mechanical strength.

Note. The tested lyft was not painted.

### 2.2. Test procedure

The X-lyft was mounted to a hydraulic cylinder with a coupling link and a master link. 1,5 m Lifting strings were mounted in the four corners of the X-lyft and also fastened in the test beam. The X-lyft was also tested with four lifting hooks attached to the special holes in the X-lyft, the lifting string were attached in those hooks. The test followed the procedure below:

1. The X-lyft was tested to a load of 5 500 kg then stopped for examination and evaluation. After 5 500 kg the X-lyft was tested to a load of 6 500 kg then unloaded and examined for permanent deformation.

Load speed: 14mm/min.

### 2.3. Test equipment and environment conditions

Test date: 2024-04-05  
Measure system: HBM MX840B  
Load cell: Omegadyne LC412-75K, RISE item no. 47h02  
Gravitation: 9,82 N/kg  
Temperature: 22 °C  
Humidity: 30-35% RF.

## 3. Result

See result in summary and in appendix 2.

### **RISE Research Institutes of Sweden AB** **Department Building and Real Estate - Production Systems and Materials**

Performed by

Examined by


Urban Haggström

Tommy Vikberg

### Appendices

1. Drawing of X-lyft
2. Load and time diagram
3. Pictures

### Appendix 1



## Appendix 2




Diagram 1. Load/time graph, X-lyft up to 54 kN with lifting strings.




Diagram 2. Load/time graph, X-lyft up to 54 kN with lifting hooks.

## Appendix 3




Figure 2. Test set up with lifting strings.



Figure 3. Test set up with lifting hooks.

Appendix 3



Figure 4. Twist in pos 2 at 6 500 kg.




Figure 5. Flatwise deformation in pos 2 after 6 500 kg.

# Verifikat

Transaktion 09222115557514541868

## Dokument

**1256915-01**

Huvuddokument

6 sidor

*Startades 2024-04-05 14:32:06 CEST (+0200) av Urban Haggström (UH)*

*Färdigställt 2024-04-08 10:53:50 CEST (+0200)*

## Signerare

**Urban Haggström (UH)**

RISE Research Institutes of Sweden AB

Org. nr 556464-6874

*urban.haggstrom@ri.se*

+46 10 516 62 46

*Signerade 2024-04-05 14:32:06 CEST (+0200)*

**Tommy Vikberg (TV)**

RISE

*tommy.vikberg@ri.se*

*Signerade 2024-04-08 10:53:50 CEST (+0200)*

Detta verifikat är utfärdat av Scrive. Information i kursiv stil är säkert verifierad av Scrive. Se de dolda bilagorna för mer information/bevis om detta dokument. Använd en PDF-läsare som t ex Adobe Reader som kan visa dolda bilagor för att se bilagorna. Observera att om dokumentet skrivs ut kan inte integriteten i papperskopian bevisas enligt nedan och att en vanlig papperutskrift saknar innehållet i de dolda bilagorna. Den digitala signaturen (elektroniska förseglingen) säkerställer att integriteten av detta dokument, inklusive de dolda bilagorna, kan bevisas matematiskt och oberoende av Scrive. För er bekvämlighet tillhandahåller Scrive även en tjänst för att kontrollera dokumentets integritet automatiskt på: <https://scrive.com/verify>

